



HORIZONTAL CARTONER

Continuous Motion Cartoner

- Flexibility for size range and quick change-over system
- Additional positive product inserter before flaps tuck-in (special for pouch)
- Machine guards with positive safety interlocks
- Sensors for monitoring carton and pouch
- Speed up to 120 cartons per min.

Applications:



Blister



Sachets



Bottles




Tubes

C180

CONTINUOUS MOTION CARTONER


Carton Size Range	
Parameter	Specification
Width (A)	50 to 105 mm
Height (B)	20 to 100 mm
Length (C)	90 to 150 mm



BETA 100

INTERMITTENT MOTION CARTONER

Carton Size Range	
Parameter	Specification
Width (A)	15 to 90 mm
Height (B)	15 to 90 mm
Length (C)	55 to 250 mm






VERTICAL CARTONER

ALPHA V6/V9/V12


- Versatile machine capable of handling a wide range of cartons
- Quick changeover (no change part)
- Automatic leaflet insertion system
- Carton closure options: one side tuck in, both side tuck in, one side glue (hot melt), both side glue (hot melt)
- Speed up to 120 cartons per min
- Product automatic loading option available

**Efficient.
Versatile.
Reliable.**

Applications:



Carton Size Range (in mm)



NICHROME INDIA LTD.

Head Office : Safire Park Galleria, 4, Pune-Mumbai Road, Shivajinagar, Pune – 411005, India.

Customer Care : +91 - 8600 97 8600 | www.nichrome.com